

LUNGO UNDERCABINET LIGHT USER INSTRUCTION


POWER ON

- Press the On/Off button once



DIMMING

- HOLD the dimming button and RELEASE when the desired light output level is achieved.



OCCUPANCY SENSOR AND TIMER USAGE

- The Lungo Light is specified and designed to save energy while providing the most amount of light at lowest power consumption. By Default, the light will stay on for 30min, but will continue turn back on immediately after detecting motion by the sensor.

LUNGO Undercabinet Light Installation Manual

INSTALLATION PROCEDURE – WOOD undercabinet mounting

Carefully plan out your installation prior to actually securing your Lungo light fixture to the mounting surface making sure that your line cord will reach the nearest electrical outlet.

TO PREVENT ELECTRIC SHOCK, MATCH WIDE BLADE OF PLUG TO WIDE SLOT
 POUR EVITER LES CHOCS ELECTRIQUES, INTRODUIRE LA LAME LA PLUS LARGE DE LA FICHE DANS LA FENTE LA PLUS LARGE

2. DO NOT ATTEMPT TO INSTALL THE FIXTURE WHILE PLUGGED IN.
 3. Select a suitable dry mounting location (for indoors only). Make sure mounting surface is completely capable of supporting the fixture.
 4. While resting the fixture on a flat surface...
 5. Place the fixture in a location where you want it mounted and mark the center of each end with a pencil. Make sure the power cable can be easily plugged in when mounted. The fixture can be mounted horizontally or vertically.
 6. Place the each of the mounting brackets inward (1.5") of the pencil marks and mark the center of the bracket hole.
 7. It is recommended that a pilot hole be drilled in the mounting surface for wood screws. Pre-drill hole in the mounting surface with a 1/16" (1.6mm) drill bit for soft woods and a 3/32" (2.4mm) drill bit for hard woods.
 8. Center the bracket over each pilot hole and drive the screws provided with the mounting hardware into the mounting surface by hand. Do not use power drill as this can strip the wood. Hand tighten until snug and the bracket is secure. DO NOT OVER TIGHTEN.
 9. With both hands, align the slot (furthest away from you) of the Lungo light fixture with the each bracket and tilt until the slot closest to you snaps in.
 10. Plug fixture into a 120VAC 60Hz outlet.
- INSTALLATION PROCEDURE - STEEL under-cabinet mounting**
1. Consult a local licensed electrician or electrical contractor if you are not sure about the installation
 2. DO NOT ATTEMPT TO INSTALL THE FIXTURE WHILE PLUGGED IN.
 3. Select a suitable dry mounting location (for indoors only). Make sure mounting surface is completely capable of supporting the fixture.
 4. While resting the fixture on a flat surface...

1. Consult a local licensed electrician or electrical contractor if you are not sure about the installation



300 Spectrum Center Drive, Ste 400 | Irvine CA 92618
Office 949 754 4040 | Fax 949-627-2757
info@mochasolutions.com | mochalighting.com

5. Attach the magnets provided with the mounting hardware by inserting the threaded post of the magnet into the mounting bracket.
6. Place the each of the mounting brackets on the rear side, inward (1.5") of each end and snap in place.
7. Place the fixture in a location where you want it mounted. See figure TBD. Make sure the power cable can be easily plugged in when mounted. The fixture can be mounted horizontally or vertically.
8. Plug fixture into a 120VAC 60Hz outlet.

Your fixture is made from quality materials that will last many years with minimal care. When cleaning, make sure you have unplugged your fixture and have allowed sufficient time for the unit to cool to room temperature. You should clean the housing and lens using a damp soft cloth. You should plug your fixture back in only after the fixture has thoroughly dried.

DISPOSAL

Follow local disposal laws. See
WWW.LAMPRECYCLE.ORG

CLEANING INSTRUCTIONS

